

STONKOTE ANDESIT SKF-636-2K SB

No. TD : S-012
Revision : 00
Effective Date : 14/09/2022

PRODUCT DESCRIPTION

STONKOTE ANDESIT SKF-636-2K SB, is 2K component solvent-based stone floor penetrating coating with nano silicone technology that can react with moisture from the atmosphere and stones to produce hard, scratch, stain and chemicals resistant surface. Enhance natural color and surface of stone.

FIELDS OF APPLICATION

- Andesite stone
- Pacitoroso
- Terrazo

PRODUCT FEATURES

1. Non slip
2. Water resistant
3. Stain and chemical resistant
4. Weather resistant
5. Abrasion resistant
6. Stone furring
7. Penetrating (non-film build)
8. Anti-fungi

PRODUCT SPECIFICATION

Type : 2K Nano Silicone Polymer

	A component	B component
Appearance	Clear	clear
Viscosity	40 ± 5 sec/Din2	40 ± 5 sec/Din2
Solid content	9 - 11 %	2,4 – 2,6 %
Specific gravity	0.98 ± 0.02 g/cc	0.98 ± 0.02 g/cc
Flash point	30°C	14°C
Packing	0.9 L; 4.5 L; 18 L in can metal	0.1 L 0.5 L 2 L in jerrycan plastic

APPLICATION

Application condition : 25 - 30°C, 40 - 60%RH
Application method : brush, roll, dip
Substrate : Andesite stone , pacitoroso , lempeng
Mixing ratio by weight : A comp. : B comp. = 9 : 1
Theoretical coverage : 15 - 20 m²/L by brush

FILM PROPERTIES

Drying time

- Dust free : 10 minutes
- Tack free : 2 – 3 hours
- Full cured : 24 hours

OTHERS

- Shelf life : Two years if stored in cool and dry condition in original sealed container.
- Storage and handling : Store in good ventilation room temperature. Exposure to direct sunlight should be avoided.

SURFACE PREPARATION

1. Clean surfaces with appropriate method. Remove all dirt and dust
2. If it necessary clean surface with Propan Fungicidal Wash or Concrete Floor Wash.

APPLICATION INFORMATION

1. Stir well **SKF-636-2K SB** before use.
2. Apply even coat of **SKF-636-2K SB** by brush or roll at coating amount 30-50 g/m².
3. Good ventilation in working area is suggested.

SAFETY PRECAUTION

1. This product is non-toxic. It does not contain any material with mercury or heavy metals. Avoid contact with the skin and eyes. Wear suitable protective clothing such as working suit, goggles, masks, and safety gloves. Use barrier cream.
2. This product is non-flammable.
3. For more information, please refer to our safety data sheet.

FIRST AID

- Eye contact : Rinse immediately with plenty of water for at least 15 minutes; seek medical advice.
- Skin contact : Wash with soap and water. If irritation occurs, seek medical advice.
- Ingestion : Provide symptomatic treatment and seek medical advice.
- Inhalation : Remove person to fresh air. Keep patient rested and give artificial respiration.

DISCLAIMER

This document contains information issued based on the best and latest of Propan's knowledge in accordance to laboratory testing and practical application experience. The end user must test the product's suitability for their specific application and purpose. Propan shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements. This document is subjected to change without further notice. Please consult Propan for any specific guidance on the suitability of this product for their needs or for any specific application practices.