LEGANZA LINEN

No. TD : L-023
Revision : 00
Effective Date : 22/12/2025

PRODUCT DESCRIPTION

Leganza Linen is a decorative textured paint designed to replicate the natural linen fabric on walls. It's made from premium acrylic emulsion. Complex application process to creates a subtle woven effect. Leganza linen offers alternative elegant with traditional finish.

USES

- Interior walls

FEATURES AND BENEFITS

- Water based, No added heavy metal
- Elegant and natural
- Classic finish
- Non toxic
- Low odour

PRODUCT DATA

Type	:	Acrylic Emulsion
Color	:	As shown in the color card
Finish	:	Satin
Solid by volume	:	± 46.0 %
Specific gravity	:	± 1.18
Theoretical coverage	:	3.00 – 5.00 m^2/L (per coat, 200-300 microns Wet Film Thickness) Depend on film thickness and wastage during application.
Drying time	:	Surface dry = 12 Hours (30° C) Depend on temperature and humidity
Packaging	:	2,5 L, 20 L
Storage stability	:	The product must be stored in accordance with national regulations. Keep the container in a dry, cool, well ventilated space and away from sources of heat and ignition. Container must be kept tightly closed. Handle with care.

APPLICATION

Thinning ratio by volume	:	- (ready for use)
Application tools	:	Roll + Brush
Wet Film thickness	:	200-300 micron (per coat)
Recoating interval	:	Minimun 12 hours (30° C)
Post treatment	:	Masking tape is used to protect surface not to be painted, e.g. door and window frames. As the dry film is elastic, cut the line with a knife or a cutter before remove the masking tape.
Cleaning	:	Wash all equipment immediately after use with water.

PT. PROPAN RAYA I.C.C | Jl. Gatot Subroto KM. 8 Tangerang 15810, Indonesia
P: +62 215930 3333 | F : +62 21 5924 694 | W : www.propanraya.com | E : info@propanraya.com

SURFACE PREPARATION

- The surface must be dry, clean, sound, and free from all contaminants. Newly build wall must be dry after 28 days old. Make sure moisture content / dampness of wall ≤ 16 % measured using Protimeter appliance and wall alkalinity (pH) 7 – 8 measured using Universal pH indicator.
- Remove all loose material or defective paint by thorough brushing and scraping using active fibre brush.
- Treat any areas affected by mould, algae, moss and lichens with **PROPAN Fungicidal Wash**.
- Repair defects with suitable filler. Use sand and cement mix for large holes and crack. Allow to dry.
- It is recommended to apply alkali resisting primer before applying this coating.

APLICATION CONDITION

Temperature	:	Minimum 15° C Maximum 50° C
Humidity maximum	:	80 % RH Provide adequate ventilation during application and drying

RECOMMENDED COATING SCHEDULE

-	Primer coat	:	DECOR Alkali Resisting Primer AR – 300 without thinning 1 x 30 microns Dry Film Thickness.
-	Base Coat	:	DECORSHIELD DW-500 thinning with 1 part of clean water to 10 parts of paint, 2 x 30 microns Dry Film.
-	Finish coat 1	:	LEGANZA LINEN Using a Roller then Brush vertically while the paint is still wet. Apply the vertical brush for a maximum of 5 minutes after applying the roller. If the area is large, apply with two people.
-	Finish coat 2	:	LEGANZA LINEN Using a Roller then Brush horizontally while the paint is still wet. Apply the horizontal brush for a maximum of 5 minutes after applying the roller. If the area is large, apply with two people.

PRECAUTION

Do not take internally. This product is non toxic and non flammable. It does not contain any material with heavy metals such as mercury and lead. Avoid contact with the skin and eyes. Higher concentrations produce more severe irritation. Wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Use barrier cream. Wash splashes from skin or eyes immediately. Read all safety, security, health and environment precautions before use.

FIRST AID

Eye contact	:	Rinse immediately with plenty of clean water. Seek medical advice.
Skin contact	:	Wash off thoroughly with plenty of water and soap immediately. Remove contaminated clothing. If irritation occurs, seek medical advice.
Inhalation	:	Remove person to fresh air, loosen collar and avoid exertion. Keep patient rested and give artificial respiration.
Ingestion	:	Provide symptomatic treatment and seek medical advice.

PT. PROPAN RAYA I.C.C | Jl. Gatot Subroto KM. 8 Tangerang 15810, Indonesia
P: +62 215930 3333 | F : +62 21 5924 694 | W : www.propanraya.com | E : info@propanraya.com

DISCLAIMER

This document contains information issued based on the best and latest of Propan's knowledge in accordance to laboratory testing and practical application experience. The end user must test the product's suitability for their specific application and purpose. Propan shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements. This document is subjected to change without further notice. Please consult Propan for any specific guidance on the suitability of this product for their needs or for any specific application practice.

PT. PROPAN RAYA I.C.C | Jl. Gatot Subroto KM. 8 Tangerang 15810, Indonesia
P: +62 215930 3333 | F : +62 21 5924 694 | W : www.propanraya.com | E : info@propanraya.com