

**PROPAN SUPER GOLD
SG – 07 WB**

NO : supergold sg-07 TD 001/1015

PROPAN Super Gold SG-07 WB is a gold-colored paint that has the look as the original gold. This product is made from acrylic emulsion combined with a special gold powder pigment, so it has durable gold sparkling, not easily to fade, good adhesion to the substrate, excellent weather resistance and excellent UV light resistance.

PRODUCT DATA

Type	: Acrylic Dispersion
Color	: Gold
Finish	: Glossy
Solid by volume	: ± 30%
Specific gravity	: ± 1.08
Theoretical coverage	: 10.0 m ² / litre (30 microns)
Drying time	: Depend on temperature and humidity Surface dry = 1 hours (30° C)
Packaging	: 0.9 litres
Storage stability	: Two year if stored cool and dry and in original not opened container (Do not store below freezing point)

APPLICATION

Thinning ratio by volume	: 10 % clean water
Application method	: Brush, Roll, Air spray or Airless spray
Dry film thickness	: 30 microns or 1.2 mils
Recommended dry film thickness	: 30 microns (1 x 30 microns)
Recoating interval	: Minimum = 2 hours (30° C), when the first paint film already dry Maximum = -
Cleaning	: Wash all equipment immediately after use with water

SURFACE PREPARATION

- The surface must be dry, clean, sound, and free from all contaminants.
- Check the surface to be painted. Remove thoroughly any contaminants and old paint that has poor adhesion to the surface. Sand old surface lightly to provide good adhesion.
- Treat any areas affected by mold, algae, moss and lichens with **PROPAN FUNGICIDAL WASH**.
- Repair defects with suitable materials.

APPLICATION CONDITION

Temperature	: Minimum 15° C Maximum 35° C
Humidity maximum	: 80 % RH
Provide adequate ventilation during application and drying.	

RECOMMENDED COATING SCHEDULE

First coat	: PROPAN SUPER GOLD SG – 07 WB
------------	--------------------------------

PT. PROPAN RAYA ICC

Marketing Office : Gatot Subroto Km. 8 Tangerang 15810 Indonesia

• Ph: +62 21 59303333

• Fax:+62 21 5904994

• www.propanraya.com

• Email: info@propanraya.com

SAFETY, SECURITY, HEALTH AND ENVIRONMENT

Do not take internally. This product is non toxic and non flammable. It does not contain any material with heavy metals such as mercury and lead. Avoid contact with the skin and eyes. Higher concentrations produce more severe irritation. Wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Use barrier cream. Wash splashes from skin or eyes immediately. Ensure adequate ventilation and fresh air entry during application and drying. If there are experiences eye watering, headaches, dizziness or difficulty breathing, leave the area to obtain fresh air or wear respiratory protection. If continued difficulty is experienced, get medical attention immediately. Do not breathe vapor or spray mist. Keep away from food, drink and animal feeding stuffs. Dangerous to fish and other aquatic life. Do not contaminate watercourses or ground. This material and its container must be disposed of in a safe way. Avoid all contact with plant life. Close container after each use and keep out of reach of children. Keep in original container, tightly closed, in cool and dry place. Avoid direct sun light. Keep from freezing. This container is used to storage the paint only. Do not apply to surfaces on which food is prepared. Wash hands and exposed skin before meals and after use. Read all safety, security, health and environment precautions before use.

First Aid :

- Skin contact : Wash off thoroughly with plenty of water and soap immediately.
Remove contaminated clothing. If irritation occurs, seek medical advice.
- Eye contact : Rinse immediately with plenty of clean water. Seek medical advice.
- Inhalation : Remove person to fresh air, loosen collar and avoid exertion.
Keep patient rested and give artificial respiration.